

WIRE EXTENSION SPRINGS



Zinc plated steel wire extension spring. Baked for a rust resistant finish and heat treated for performance and longevity. Ideal for a wide variety of uses in homes, the shop, on the farm or ranch, small businesses or light industry such as screen doors, chaise lounges, toys, lawn and garden equipment, industrial and farm equipment, business machines, cars, trucks, boats, RV's, etc. Packs of 2.

CAT#	LENGTH	WIRE DIAMETER	OUTER DIAMETER	MAX LOAD (LBS.)	NUMBER IN PACKAGE
72506	1.5"	.015"	.125"	1.4 lbs.	2
72507	1.5"	.02"	.156"	2.7 lbs.	2
72508	1.5"	.023"	.218"	2.9 lbs.	2
72509	1.5"	.035"	.25"	8.4 lbs.	2
72510	1.5"	.025"	.281"	2.8 lbs.	2
72511	1.5"	.02"	.312"	1.4 lbs.	2
72512	1.5"	.028"	.343"	3.6 lbs.	2
72513	1.5"	.028"	.437"	2.5 lbs.	2
72514	1.5"	.047"	.437"	11 lbs.	2
72540	1.625"	.08"	.5"	35 lbs.	2
72515	1.875"	.014"	.125"	1.3 lbs.	2
72516	1.875"	.02"	.156"	2.2 lbs.	2
72517	1.875"	.02"	.25"	1.7 lbs.	2
72518	1.875"	.025"	.281"	4.7 lbs.	2
72519	1.875"	.035"	.25"	8.4 lbs.	2
72520	1.875"	.025"	.281"	4.7 lbs.	2
72521	1.875"	.025"	.343"	2.3 lbs.	2
72522	1.875"	.028"	.437"	2.5 lbs.	2
72523	1.875"	.047"	.437"	11 lbs.	2
72532	2"	.062"	.437"	19 lbs.	2
72541	2"	.105"	.75"	60 lbs.	2
72542	2.25"	.105"	.75"	60 lbs.	2
72543	2.437"	.105"	.75"	50 lbs.	2
72524	2.5"	.018"	.125"	2.5 lbs.	2
72525	2.5"	.02"	.156"	2.7 lbs.	2
72526	2.5"	.025"	.187"	4.2 lbs.	2
72527	2.5"	.016"	.25"	0.87 lbs.	2
72528	2.5"	.02"	.25"	1.7 lbs.	2
72529	2.5"	.035"	.25"	8.4 lbs.	2
72530	2.5"	.028"	.437"	2.5 lbs.	2

CAT#	LENGTH	WIRE DIAMETER	OUTER DIAMETER	MAX LOAD (LBS.)	NUMBER IN PACKAGE
72531	2.5"	.047"	.437"	11 lbs.	2
72534	2.5"	.072"	.625"	19 lbs.	2
72544	2.625"	.105"	.75"	50 lbs.	2
72538	2.75"	.035"	.437"	3.3 lbs.	2
72545	2.875"	.072"	.562"	22 lbs.	2
72549	2.875"	.105"	.75"	60 lbs.	2
72535	3"	.054"	.562"	9.2 lbs.	2
72536	3"	.028"	.312"	3.5 lbs.	2
72550	3.125"	.105"	.75"	50 lbs.	2
72537	3.25"	.025"	.25"	3.1 lbs.	2
72546	3.25"	.072"	.625"	19 lbs.	2
72533	3.5"	.054"	.437"	12 lbs.	2
72539	3.5"	.047"	8.4"	2 lbs.	2
72548	3.5"	.062"	.75"	11 lbs.	2
72551	3.75"	.105"	.75"	50 lbs.	2
72555	3.75"	.041"	.375"	6.5 lbs.	2
72547	4"	.047"	.562"	6.5 lbs.	2
72552	4"	.035"	.375"	3.9 lbs.	2
72568	4"	.12"	.812"	66 lbs.	2
72554	4.5"	.028"	.375"	2.9 lbs.	2
72556	4.5"	.041"	.468"	5.2 lbs.	2
72557	4.5"	.062"	.5"	16 lbs.	2
72567	4.5"	.091"	.812"	29 lbs.	2
72559	4.75"	.091"	.687"	35 lbs.	2
72553	5"	.035"	.25"	6 lbs.	2
72558	5"	.072"	.5"	25 lbs.	2
72579	5"	.035"	.375"	5.4 lbs.	2
72580	5"	.032"	.312"	5.2 lbs.	2
72581	5"	.035"	.312"	6.6 lbs.	2
72569	5.5"	.12"	1.062"	49 lbs.	1

WIRE EXTENSION SPRINGS (CONTINUED)

CAT#	LENGTH	WIRE DIAMETER	OUTER DIAMETER	MAX LOAD (LBS.)	NUMBER IN PACKAGE
72578	5.5"	.062"	.375"	23 lbs.	2
72582	5.5"	.12"	1.062"	49 lbs.	1
72560	6"	.072"	.562"	22 lbs.	2
72561	6"	.035"	.25"	6 lbs.	2
72562	6"	.028"	.312"	3.9 lbs.	2
72570	6"	.091"	.875"	26 lbs.	1
72563	6.5"	.047"	.375"	10 lbs.	2
72564	6.5"	.054"	.625"	8.3 lbs.	2
72572	6.5"	.162"	1.25"	100 lbs.	1
72577	6.5"	.091"	6.5"	31 lbs.	1
72571	7"	.105"	1.062"	33 lbs.	1
72573	7"	.135"	1"	75 lbs.	1
72576	7.5"	.091"	1.125"	20 lbs.	1
72574	8.5"	.08"	1.062"	15 lbs.	1
72575	8.5"	.148"	1.125"	87 lbs.	1
72587	8.5"	.047"	5"	7.2 lbs.	1

CAT#	LENGTH	WIRE DIAMETER	OUTER DIAMETER	MAX LOAD (LBS.)	NUMBER IN PACKAGE
72588	8.5"	.047"	.437"	8.4 lbs.	1
72589	8.5"	.091"	.625"	39 lbs.	1
72590	8.5"	.054"	.562"	9.2 lbs.	1
72591	8.5"	.062"	.625"	13 lbs.	1
72592	8.5"	.08"	.625"	27 lbs.	1
72593	8.5"	.062"	.875"	8.8 lbs.	1
72594	8.5"	.105"	.875"	41 lbs.	1
72596	8.5"	.12"	1"	52 lbs.	1
72595	9"	.135"	.875"	87 lbs.	1
72597	10"	.148"	1.25"	77 lbs.	1
72586	10.25"	.041"	.437"	5.5 lbs.	1
72583	11.5"	.135"	1.5"	47 lbs.	1
72584	12"	.105"	1"	35 lbs.	1
72585	12"	.135"	1.062"	69 lbs.	1
72565	16"	.105"	1.125"	31 lbs.	1
72566	16.5"	.054"	.562"	9.2 lbs.	1